

## TECHNICAL DATA SHEET

### ENG-HA-FRE HAMPTON RANGE: FRENCH WHITE

#### PRODUCT SPECIFICATIONS

|               |                                                                                                          |
|---------------|----------------------------------------------------------------------------------------------------------|
| PRODUCT RANGE | HAMPTON RANGE                                                                                            |
| COLOUR        | FRENCH WHITE                                                                                             |
| PRODUCT CODE  | ENG-HA-FRE                                                                                               |
| CONSTRUCTION  | MULTI-LAYERED ENGINEERED                                                                                 |
| BACKING       | BIRCH PLYWOOD                                                                                            |
| SPECIES       | EUROPEAN OAK                                                                                             |
| PATTERN       | 1 STRIP                                                                                                  |
| BOX SIZE      | 2.888 m <sup>2</sup>                                                                                     |
| EDGE          | BEVEL                                                                                                    |
| PROFILE       | TONGUE AND GROOVE                                                                                        |
| FINISH        | UV LACQUERED                                                                                             |
| TOP LAYER     | 2mm EUROPEAN OAK LAMELLA                                                                                 |
| THICKNESS     | 12mm                                                                                                     |
| WIDTH         | 190mm                                                                                                    |
| LENGTH        | 1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths) |



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

#### INSTALLATION METHODS

|                         |     |
|-------------------------|-----|
| DIRECT STICK            | YES |
| FLOATING ON UNDERLAY    | YES |
| OVER UNDERFLOOR HEATING | YES |

#### WARRANTY

|             |                     |
|-------------|---------------------|
| RESIDENTIAL | LIFETIME STRUCTURAL |
| COMMERCIAL  | 10 YEARS STRUCTURAL |

#### AUSTRALIAN STANDARDS

|                                                  |                       |
|--------------------------------------------------|-----------------------|
| ACOUSTIC RATING                                  | DEPENDENT ON UNDERLAY |
| SLIP RATING AS 4586-2013                         | P4                    |
| FORMELDELHYDE /VOC RATING                        | E1 / LOW VOC          |
| CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003 | 3.1 kW/m <sup>2</sup> |
| JANKA HARDNESS RATING                            | 1120                  |

