



TECHNICAL DATA SHEET

ENG-SI-APOSELECT SIGNATURE OAK RANGE: APOLLO SELECT

PRODUCT SPECIFICATIONS

| 1 RODGOT OF EGILIOATIONS | | |
|--------------------------|--|--|
| PRODUCT RANGE | SIGNATURE OAK RANGE | |
| COLOUR | APOLLO SELECT | |
| PRODUCT CODE | ENG-SI-APOSELECT | |
| CONSTRUCTION | MULTI-LAYERED ENGINEERED | |
| BACKING | EUCALYPTUS | |
| SPECIES | EUROPEAN OAK | |
| PATTERN | 1 STRIP | |
| BOX SIZE | 2.42m ² | |
| EDGE | BEVEL | |
| PROFILE | TONGUE AND GROOVE | |
| FINISH | 10% MATTE – 9 COATS TREFFERT LACQUER | |
| TOP LAYER | 4mm EUROPEAN OAK LAMELLA | |
| THICKNESS | 15mm | |
| WIDTH | 220mm | |
| LENGTH | 2100mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths) | |
| | | |



The photograph used in this sheet is intended as an illustration. Colours will vary between batches in stock.

INSTALLATION METHODS

| DIRECT STICK | YES | |
|----------------------------|-----------------------|--|
| FLOATING ON UNDERLAY | YES | |
| OVER UNDERFLOOR HEATING | YES WITH RESTRICTIONS | |

WARRANTY

| RESIDENTIAL | LIFETIME STRUCTURAL |
|-------------|---------------------|
| COMMERCIAL | 10 YEARS STRUCTURAL |

AUSTRALIAN STANDARDS

| ACOUSTIC RATING | DEPENDENT ON UNDERLAY |
|--|-----------------------|
| SLIP RATING AS 4586-2013 | P3 |
| FORMELDELHYDE RATING | E1 |
| CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003 | 4.6 kW/m ² |
| JANKA HARDNESS RATING | 1120 |







www.woodpeckerflooring.com.au Page 1 of 1