



TECHNICAL DATA SHEET

ENG-AU-BLA-136S

SIGNATURE AUSTRALIAN RANGE: BLACKBUTT SATIN

PRODUCT SPECIFICATIONS

| I KODOOT OF LOTTIC | Allono | | |
|--------------------|---|--|--|
| PRODUCT RANGE | SIGNATURE AUSTRALIAN RANGE | | |
| COLOUR | BLACKBUTT | | |
| PRODUCT CODE | ENG-AU-BLA-136S | | |
| CONSTRUCTION | MULTI-LAYERED ENGINEERED | | |
| BACKING | EUCALYPTUS PLYWOOD | | |
| GRADE | STANDARD AND BETTER | | |
| PATTERN | 1 STRIP | | |
| BOX SIZE | VARIES WITH BATCH | | |
| EDGE | SQUARE | | |
| PROFILE | TONGUE AND GROOVE | | |
| FINISH | LACQUER | | |
| TOP LAYER | 3mm BLACKBUTT LAMELLA | | |
| THICKNESS | 14mm | | |
| WIDTH | 136mm | | |
| LENGTH | 1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths) | | |



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

| INICI | - A I | | TIC | | ACT | 110 | 200 |
|-------|--------------|-----|-----|------|-----|-----|-----|
| INST | IAL | .LA | HU | JN N | ИEI | HU | ID2 |

| DIRECT STICK | YES |
|----------------------------|----------------------|
| FLOATING ON UNDERLAY | YES |
| OVER UNDERFLOOR HEATING | YES WITH LIMITATIONS |

| RESIDENTIAL | LIFETIME STRUCTURAL | |
|-------------|---------------------|---|
| COMMERCIAL | 10 YEARS STRUCTURAL | _ |

AUSTRALIAN STANDARDS

| ACOUSTIC RATING | DEPENDENT ON UNDERLAY |
|--|-----------------------|
| SLIP RATING AS 4586-2013 | P2 |
| FORMELDELHYDE RATING | E1 |
| CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003 | 3.2 kW/m ² |
| JANKA HARDNESS RATING | 9.1kN |







WARRANTY