HEAD OFFICE
25 Sundercombe Street,
Osborne Park, WA, 6017
AUSTRALIA

+61 (08) 6142 1511

TECHNICAL DATA SHEET

ENG-SA-DUN **ESCO SERIES**
DUNE

PRODUCT SPECIFICATIONS

PRODUCT RANGE	Esco Series
COLOUR	Dune
PRODUCT CODE	ENG-SA-DUN
GRADE	Select
CONSTRUCTION	Multi-layered engineered
BACKING	Birch
SPECIES	European Oak
BOX SIZE	Varies
EDGE	Micro Bevel
PROFILE	Tongue and Groove
FINISH	Osmo Polyx Oil
TOP LAYER	4mm European Oak Lamella
THICKNESS	14mm
WIDTH	225mm
LENGTH	1200-2400mm

The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	Yes
FLOATING ON UNDERLAY	Yes
OVER UNDERFLOOR HEATING	Yes, with restrictions

WARRANTY

RESIDENTIAL	Lifetime Structural
COMMERCIAL	10 Years Structural

AUSTRALIAN STANDARDS

ACOUSTIC RATING	Dependent on underlay
SLIP RATING AS 4586-2013	P3
FORMALDEHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	3.0 kW/m2
JANKA HARDNESS RATING	1120