



TECHNICAL DATA SHEET

ENG-AU-SPO-135MB

SIGNATURE AUSTRALIAN RANGE: SPOTTED GUM SMOOTH MATTE

PRODUCT SPECIFICATIONS

PRUDUCI SPECIFIC	JA I IUNG
PRODUCT RANGE	SIGNATURE AUSTALIAN RANGE
COLOUR	SPOTTED GUM
PRODUCT CODE	ENG-AU-SPO-135MB
CONSTRUCTION	3-LAYERED ENGINEERED
BACKING	HEVEA
GRADE	STANDARD AND BETTER
PATTERN	1 STRIP
BOX SIZE	1.474m2/B0X
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	SMOOTH MATTE
TOP LAYER	3mm SPOTTED GUM LAMELLA
THICKNESS	14mm
WIDTH	135mm
LENGTH	1820mm (Product contains split lengths, with up to 32% nested)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES	
FLOATING ON UNDERLAY	YES	
OVER UNDERFLOOR HEATING	YES WITH LIMITATIONS	

RESIDENTIAL LIFETIME STRUCTURAL

COMMERCIAL 10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P2
FORMELDELHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	3.2 kW/m ²
JANKA HARDNESS RATING	11kN







www.woodpeckerflooring.com.au Page 1 of 1