



TECHNICAL DATA SHEET

ENG-AU-BLA-130CB

SIGNATURE AUSTRALIAN RANGE: BLACKBUTT CHARACTER SATIN

PRODUCT SPECIFICATIONS

PRODUCT SPECIF	ICA I IUNO		
PRODUCT RANGE	SIGNATURE AUSTALIAN RANGE		
COLOUR	BLACKBUTT		
PRODUCT CODE	ENG-AU-BLA-130CB		
CONSTRUCTION	MULTI-LAYERED ENGINEERED		
BACKING	EUCALYPTUS PLYWOOD		
GRADE	CHARACTER		
PATTERN	1 STRIP		
BOX SIZE	VARIES WITH BATCH		
EDGE	BEVEL		
PROFILE	TONGUE AND GROOVE		
FINISH	LACQUER		
TOP LAYER	3mm BLACKBUTT LAMELLA		
THICKNESS	14mm		
WIDTH (mm)	130		
LENGTH	1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)		
	7 M		



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES WITH LIMITATIONS

١	AI	Λ	D	D	٨	N	ΤY	•
١	N	А	π	π.	н	IV		

RESIDENTIAL	LIFETIME STRUCTURAL	
COMMERCIAL	10 YEARS STRUCTURAL	

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P2
FORMELDELHYDE	 F1
RATING CRITICAL HEAT	
FLUX (CHF) MEAN	3.2 kW/m^2
AS/ISO 9239.1-2003 JANKA HARDNESS	
RATING	9.1kN





