



TECHNICAL DATA SHEET

LAM-TAS-BLA, LAM-TAS-CAN, LAM-TAS-CHE, LAM-TAS-OXF, LAM-TAS-RIV, LAM-TAS-SAN, LAM-TAS-SPO, LAM-TAS-SUN **TASMAN SERIES**

PRODUCT SPECIFICATIONS

| | 271110110 |
|---------------|---|
| PRODUCT RANGE | TASMAN SERIES |
| COLOURS | BLACKBUTT, CANVAS, CHESTER, OXFORD, RIVIERE, SANDALFORD, |
| | SPOTTED GUM, SUNFLOWER |
| PRODUCT CODE | LAM-TAS- |
| CONSTRUCTION | WATER RESISTANT HDF |
| BACKING | 2mm HDPE FOAM |
| SPECIES | N/A |
| PATTERN | 1 STRIP |
| BOX SIZE | 1.4896 m ² |
| EDGE | MICRO BEVEL |
| PROFILE | CLICK |
| FINISH | Brushed Finish for Blackbutt & Spotted |
| | Gum |
| | 4D EIR finish for all the other colours |
| THICKNESS | 10mm + 2mm EVA |
| WIDTH | 196mm |
| LENGTH | 1520mm |



Shown Above: Oxford

Please go to website for swatches of other colours in this range. The photograph used in this sheet is intended as an illustration. Colours will vary between batches in stock.

INSTALLATION METHODS

| DIRECT STICK | NO |
|----------------------------|-----|
| FLOATING ON UNDERLAY | YES |
| OVER UNDERFLOOR HEATING | NO |

WARRANTY

| RESIDENTIAL | 30 YEARS STRUCTURAL |
|---------------------|---------------------|
| LIGHT COMMERCIAL | 10 YEARS STRUCTURAL |

AUSTRALIAN STANDARDS

| SLIP RATING | P3 |
|----------------------|-----------------------|
| FORMELDELHYDE RATING | Carb Phase 2 |
| AS/ISO 9239.1-2003 | 7.7 kW/m ² |







Page 1 of 1 www.woodpeckerflooring.com.au