



TECHNICAL DATA SHEET

ENG-AU-BLA-130SB

SIGNATURE AUSTRALIAN RANGE: BLACKBUTT SATIN

PRODUCT SPECIFICATIONS

| PRODUCT SPECIF | ICATIONS |
|----------------|--|
| PRODUCT RANGE | SIGNATURE AUSTALIAN RANGE |
| COLOUR | BLACKBUTT |
| PRODUCT CODE | ENG-AU-BLA-130SB |
| CONSTRUCTION | MULTI-LAYERED ENGINEERED |
| BACKING | EUCALYPTUS PLYWOOD |
| GRADE | STANDARD AND BETTER |
| PATTERN | 1 STRIP |
| BOX SIZE | VARIES WITH BATCH |
| EDGE | BEVEL |
| PROFILE | TONGUE AND GROOVE |
| FINISH | LACQUER |
| TOP LAYER | 3mm BLACKBUTT LAMELLA |
| THICKNESS | 14mm |
| WIDTH (mm) | 130 |
| LENGTH | 1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths) |
| | (/ |



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

| 7 | |
|-------------------------|----------------------|
| DIRECT STICK | YES |
| FLOATING ON UNDERLAY | YES |
| OVER UNDERFLOOR | YES WITH LIMITATIONS |

| W | Λ | D | D | ۸۱ | N | T١ | v |
|---|---|---|----|----|----|----|---|
| W | м | л | n. | н | IV | | I |

| *********** | | |
|-------------|---------------------|--|
| RESIDENTIAL | LIFETIME STRUCTURAL | |
| COMMERCIAL | 10 YEARS STRUCTURAL | |

AUSTRALIAN STANDARDS

| ACOUSTIC RATING | DEPENDENT ON UNDERLAY |
|-----------------------------------|-----------------------|
| SLIP RATING AS 4586-2013 | P2 |
| FORMELDELHYDE | F1 |
| RATING CRITICAL HEAT | |
| FLUX (CHF) MEAN | 3.2 kW/m^2 |
| AS/ISO 9239.1-2003 JANKA HARDNESS | |
| RATING | 9.1kN |







www.woodpeckerflooring.com.au Page 1 of 1