



## **TECHNICAL DATA SHEET**

ENG-AU-JAR-136SB | ENG-AU-JAR-180SB SIGNATURE AUSTRALIAN RANGE: JARRAH SATIN

## PRODUCT SPECIFICATIONS

PRODUCT SPECIF	ICATIONS
PRODUCT RANGE	SIGNATURE AUSTALIAN RANGE
COLOUR	JARRAH
PRODUCT CODE	ENG-AU-JAR-136SB
	ENG-AU-JAR-180SB
CONSTRUCTION	MULTI-LAYERED ENGINEERED
BACKING	EUCALYPTUS PLYWOOD
SPECIES	EUCALYPTUS MARGINATA
PATTERN	1 STRIP
BOX SIZE	VARIES WITH BATCH
EDGE	BEVELLED
PROFILE	TONGUE AND GROOVE
FINISH	LACQUER
TOP LAYER	3mm JARRAH LAMELLA
THICKNESS	14mm
WIDTH (mm)	136mm   180mm
	UP TO 2100mm (Product contains split
LENGTH	lengths, with up to 25% shorter boards.
	These may be half or 1/3 lengths)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

## **INSTALLATION METHODS**

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES

WARRANTY	
----------	--

***********		L
RESIDENTIAL	LIFETIME STRUCTURAL	
COMMERCIAL	10 YEARS STRUCTURAL	

## **AUSTRALIAN STANDARDS**

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P2
FORMELDELHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	3.2 kW/m <sup>2</sup>
JANKA HARDNESS RATING	8.5kN







www.woodpeckerflooring.com.au Page 1 of 1