



TECHNICAL DATA SHEET

ENG-HA-MAR HAMPTON RANGE: MARINA

PRODUCT SPECIFICATIONS

| HAMPTON RANGE |
|--|
| MARINA |
| ENG-HA-MAR |
| MULTI-LAYERED ENGINEERED |
| BIRCH PLYWOOD |
| EUROPEAN OAK |
| 1 STRIP |
| 2.888 m ² |
| BEVEL |
| TONGUE AND GROOVE |
| UV OIL |
| 2mm EUROPEAN OAK LAMELLA |
| 12mm |
| 190mm |
| 1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths) |
| |



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

| DIRECT STICK | YES | | |
|----------------------------|-----|--|---|
| FLOATING ON UNDERLAY | YES | | R |
| OVER UNDERFLOOR HEATING | YES | | |

WARRANTY

| RESIDENTIAL | LIFETIME STRUCTURAL |
|-------------|---------------------|
| COMMERCIAL | 10 YEARS STRUCTURAL |

AUSTRALIAN STANDARDS

| ACOUSTIC RATING | DEPENDENT ON UNDERLAY | |
|--------------------|-----------------------|--|
| SLIP RATING | P4 | |
| AS 4586-2013 | 1 4 | |
| FORMELDELHYDE | F1 | |
| RATING | | |
| CRITICAL HEAT | | |
| FLUX (CHF) MEAN | 3.1 kW/m ² | |
| AS/ISO 9239.1-2003 | | |
| JANKA HARDNESS | 1120 | |
| RATING | | |





