



# **TECHNICAL DATA SHEET**

# **ENG-SI-ADI SIGNATURE OAK RANGE: ADIRONDACK**

#### **PRODUCT SPECIFICATIONS**

I KODOCI SI EC	
PRODUCT RANGE	SIGNATURE OAK RANGE
COLOUR	ADIRONDACK
PRODUCT CODE	ENG-SI-ADI
CONSTRUCTION	MULTI-LAYERED ENGINEERED
BACKING	EUCALYPTUS
SPECIES	EUROPEAN OAK
PATTERN	1 STRIP
BOX SIZE	2.42m <sup>2</sup>
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	10% MATTE – 9 COATS TREFFERT LACQUER
TOP LAYER	4mm EUROPEAN OAK LAMELLA
THICKNESS	15mm
WIDTH	220mm
LENGTH	2100mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

### **INSTALLATION METHODS**

MOTALLATION METHODS				_		
DIRECT STICK	YES					
FLOATING ON UNDERLAY	YES					
OVER UNDERFLOOR HEATING	YES WITH RESTRI	CTIO	NS			

/ \		\	- (
WA	DE	) A N	ITY
WWA	VR 1	СΔΝ	

***************************************	
RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

#### **AUSTRALIAN STANDARDS**

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING	P3
AS 4586-2013	r 3
FORMELDELHYDE	F1
RATING	LI
CRITICAL HEAT	
FLUX (CHF) MEAN	4.6 kW/m <sup>2</sup>
AS/ISO 9239.1-2003	
JANKA HARDNESS	1120
RATING	1120







www.woodpeckerflooring.com.au Page 1 of 1